

Seismic Transmitter

Product Datasheet

Bently Nevada* Asset Condition Monitoring

Description

The 177230 Seismic Transmitter combines a reliable basic protection solution with the support and service of GE products. The transducer is a simple, loop-powered device whose ease of installation and maintenance may reduce training and service costs. When integrated into the PLC or controls system of an overall plant asset condition monitoring solution, the transducer will help you better manage downtime, optimize maintenance planning, and avoid unforeseen catastrophic failures of machinery assets.

Features of the 177230 Seismic Transducer include:



- Ease of implementation and use
 - Interfaces with PLCs and control systems (like DCS and SCADA)
 - Provides a quick learning curve for operations and maintenance -through a familiar interface similar to that for connecting other PLC or control system inputs
 - Requires no field configuration or adjustments
 - Needs few additional parts for a complete system
 - Includes technical support for customers on how to monitor their equipment
 - Includes self-test
 - Incorporates protected interface
 - Supports a variety of interface cables
- Data Quality
 - Provides accurate and repeatable data
 - Uses simple data format
 - Provides raw vibration signal for verification and analysis
- EHS Compliant
 - Implements safe and ergonomic design
 - Supports access to hazardous areas
- Incorporates robust CM design for reliability
- Implements Industry standard 4 to 20mA loop-powered transmitter



imagination at work

Part Number 177232-01
Rev. M

Page 1 of 7

Specifications

Electrical

Sensitivity – Main loop (Signal One)

0.0 to 12.7 mm/s (0 to 0.5 in/s)
0.0 to 25.4 mm/s (0 to 1.0 in/s)
0.0 to 50.8 mm/s (0 to 2.0 in/s)
± 10% FS, broadband rms (root mean square)
[4 ± 0.3 mA equals 0.0 mm/s and
20 ± 2 mA equals 25.4 mm/s]

Output Format, Pin A Referenced to Pin B

4 to 20 mA current loop Velocity vibration

Excitation Voltage

12 to 30 Vdc (current limited to 40 mA)

Note: This product is for use with PLCs, DCS and SCADA systems that have internal power supply that are typically current limited in the range of 30 mA to 35 mA.

Settling Time

Less than 15 seconds within 2% of final value

Connector Wiring Convention

Pin A: 4-20 mA Positive Loop
Pin B: 4-20 mA Negative Loop and common for Dynamic Signal
Pin C: Dynamic Signal in voltage, unbuffered

Frequency Response

10 Hz to 1 kHz (600 cpm to 60 kcpm) ± 10%

Sensitivity – Dynamic Signal (Signal Two)

10.2 mV/m/s² (100 mV/g) ± 20%

Output Format, Pin C Referenced to Pin B

Voltage, Acceleration vibration

Note: The Dynamic Signal Negative (Pin B) requires isolation from any grounding. If this terminal is grounded, the 4-20 mA loop will short, resulting in no output.

Frequency Response

1Hz to 10 kHz (60cpm to 600 kcpm) ± 3 dB

Linearity

±1%

Output Bias Referenced to Pin B

2.5 V ± 0.1 V

Full Scale Range

147 m/s² (15 g's) peak

Velocity Range (see Option AA and BB)

0 – 12.7 mm/s (0 – 0.5 in/s)
0 – 25.4 mm/s (0 – 1.0 in/s)
0 – 50.8 mm/s (0 – 2.0 in/s)

Mounted Resonant Frequency

Greater than 12 kHz

Transverse Sensitivity

Less than 5% of sensitivity

Sensing Element Type

Ceramic / Shear

Ordering Information

For the detailed listing of country and product specific approvals, refer to the **Approvals Quick Reference Guide**, document 108M1756, at www.GEmeasurement.com.

Seismic Transmitter

177230-AA-BB-CC

Option Descriptions

AA:	The following are standard lengths	
	Feet	Metres (approx.)
	12	3.6
	15	4.5
	17	5.0
	20	6.0
	25	7.6
	30	9.0
	33	10.0
	50	15.2
	99	30.0
NOTE: Non-standard/custom lengths can also be ordered at additional cost		

Measurement Range

00	0 – 12.7 mm/s (0 – 0.5 in/s)
01	0 – 25.4 mm/s (0 – 1.0 in/s)
02	0 – 50.8 mm/s (0 – 2.0 in/s)

BB: Frequency

01	10 Hz to 1 kHz (600 to 60 kcps) rms
02	3 Hz to 1 kHz (180 to 60 kcps) pk

CC: Approvals

05	Multiple Approvals (CSA/NRTL/C, ATEX/IECEX)
-----------	---

Interconnect Cable without Armor

16925-AA

Option A description

A: Length in feet

Order in increments of 1 foot (0.3 m)
Minimum length: 3 feet (0.91 m)
Maximum length: 99 feet (30.2m)
Example: 25 = 25 feet

The following are standard lengths	
Feet	Metres (approx.)
12	3.6
15	4.5
17	5.0
20	6.0

25	7.6
30	9.0
33	10.0
50	15.2
99	30.0

NOTE: Non-standard/custom lengths can also be ordered at additional cost

Interconnect Cable with Armor

16710-AA

Option A description

A: Length in feet

Order in increments of 1 foot (0.3 m)

Minimum length: 3 feet (0.91 m)

Maximum length: 99 Feet (30.2m)

Example: 25 = 25 feet

Accessories

The parts listed below are possible vendor sources for the supporting hardware. You can use this information as a reference and select the vendor that you wish to use.

3-Pin Connector (MIL-C-5015):

Base

Cannon (ITT industries):

www.ittcannon.com

P/N: CA3106R-10SL-3S F97 or

P/N: MS3106R-10SL-3S

Shell

Sunbank Co.

www.sunbankcorp.com

Glenair, Inc.

www.glenair.com

Contact a vendor with above part number and ask for their part that fits your application

Wire (3-wire with shield)

3-conductor 18 to 22 AWG cables with a 0.01" minimum outer jacket and inner wire insulation, and 80% minimum coverage shield. Insulation rating should be 600 V minimum.