SIEMENS

Data sheet

6ES7422-1BL00-0AA0

SIMATIC S7-400, digital output SM 422, isolated 32 DO; 24 V DC, 0.5 A $\,$



Figure similar

Supply voltage	
Load voltage L+	
Rated value (DC)	24 V
 permissible range, lower limit (DC) 	20.4 V
• permissible range, upper limit (DC)	28.8 V
Input current	
from load voltage L+ (without load), max.	30 mA
from backplane bus 5 V DC, max.	200 mA
Power loss	
Power loss, typ.	4 W
Digital outputs	
Number of digital outputs	32
Short-circuit protection	Yes; Clocked electronically
 Response threshold, typ. 	0.7 to 1.5 A
Limitation of inductive shutdown voltage to	-27 V
Controlling a digital input	Yes; possible

Switching capacity of the outputs	
• on lamp load, max.	5 W
Load resistance range	
• lower limit	48 Ω
• upper limit	4 kΩ
Output voltage	
● for signal "1", min.	L+ (-0.3 V)
Output current	
● for signal "1" rated value	0.5 A
• for signal "1" permissible range, min.	5 mA
• for signal "1" permissible range, max.	0.6 A
• for signal "0" residual current, max.	0.3 mA
Output delay with resistive load	
• "0" to "1", max.	1 ms
• "1" to "0", max.	1 ms
Parallel switching of two outputs	
• for uprating	Yes; possible (only outputs of the same group)
 for redundant control of a load 	Yes; possible (only outputs of the same group)
Switching frequency	
with resistive load, max.	100 Hz
with inductive load, max.	0.5 Hz
 with inductive load (acc. to IEC 60947-5-1, DC13), max. 	2 Hz; 2 Hz at 0.3 A; 0.5 Hz at 0.5 A
• on lamp load, max.	10 Hz
Total current of the outputs (per group)	
all mounting positions	
— up to 40 °C, max.	4 A
— up to 60 °C, max.	2 A; 8 adjacent outputs each
Cable length	
• shielded, max.	1 000 m
• unshielded, max.	600 m
Interrupts/diagnostics/status information	
Diagnostics function	No
Potential separation	
Potential separation digital outputs	
• between the channels	No
between the channels, in groups of	32
• between the channels and backplane bus	Yes
Isolation	
Isolation tested with	500 V DC

Dimensions	
Width	25 mm
Height	290 mm
Depth	210 mm
Weights	
Weight, approx.	600 g
last modified:	06/09/2020 C